



MULTI



TABLEAUX DE COMBINAISON

Groupe 2 sorties

FROID											
Combinaison Unité Int		Capacité nominale (kW)		Capacité frigorifique (kW)			Puissance absorbée (kW)			SEER	Class. Energ.
A	B	A	B	Nom.	Max	Min	Nom.	Max			
7	-	2.0	-	1.4	2.0	2.9	0.4	0.6	0.7	-	-
9	-	2.5	-	1.4	2.5	3.2	0.4	0.7	0.9	-	-
12	-	3.5	-	1.4	3.5	3.9	0.4	1.1	1.3	-	-
18	-	5.0	-	1.6	5.0	5.5	0.5	1.5	1.9	-	-
7	7	2.1	2.1	2.1	4.2	5.6	0.5	1.2	2.0	6.1	A++
7	9	2.1	2.6	2.1	4.7	5.8	0.5	1.5	2.0	6.1	A++
7	12	1.9	3.3	2.1	5.2	6.4	0.5	1.6	2.0	6.1	A++
9	9	2.7	2.7	2.1	5.3	6.4	0.5	1.6	2.0	6.1	A++
9	12	2.3	3.0	2.1	5.3	6.4	0.5	1.6	2.0	6.1	A++
12	12	2.7	2.7	2.1	5.3	6.4	0.5	1.6	2.0	6.1	A++

CHAUD											
Combinaison Unité Int		Capacité nominale (kW)		Capacité calorifique (kW)			Puissance absorbée (kW)			SCOP	Class. Energ.
A	B	A	B	Min.	Nom.	Max	Min	Nom	Max		
7	-	2.0	-	1.4	2.0	2.9	0.4	0.6	0.7	-	-
9	-	2.5	-	1.4	2.5	3.2	0.4	0.7	0.9	-	-
12	-	3.5	-	1.4	3.5	3.9	0.4	1.1	1.3	-	-
18	-	5.0	-	1.6	5.0	5.5	0.5	1.5	1.9	-	-
7	7	2.1	2.1	2.1	4.2	5.6	0.5	1.2	2.0	6.1	A++
7	9	2.1	2.6	2.1	4.7	5.8	0.5	1.5	2.0	6.1	A++
7	12	1.9	3.3	2.1	5.2	6.4	0.5	1.6	2.0	6.1	A++
9	9	2.7	2.7	2.1	5.3	6.4	0.5	1.6	2.0	6.1	A++
9	12	2.3	3.0	2.1	5.3	6.4	0.5	1.6	2.0	6.1	A++
12	12	2.7	2.7	2.1	5.3	6.4	0.5	1.6	2.0	6.1	A++

Groupe 3 sorties

FROID													
Combinaison Unité Int			Capacité nominale (kW)			Capacité frigorifique (kW)			Puissance absorbée (kW)			SEER	Class. Energ.
A	B	C	A	B	C	Min.	Nom.	Max	Min	Nom	Max		
7	-	-	2.0	-	-	1.6	2.0	2.9	0.4	0.6	0.8	-	-
9	-	-	2.5	-	-	1.6	2.5	3.2	0.4	0.8	1.0	-	-
12	-	-	3.5	-	-	1.6	3.5	3.9	0.4	1.1	1.3	-	-
18	-	-	5.0	-	-	1.8	5.0	6.5	0.5	1.5	1.8	-	-
7	7	-	2.1	2.1	-	2.2	4.2	6.3	0.6	1.3	2.1	5.6	A+
7	9	-	2.1	2.6	-	2.2	4.7	6.7	0.6	1.5	2.2	5.6	A+
7	12	-	2.0	3.3	-	2.2	5.3	7.1	0.6	1.6	2.4	5.6	A+
7	18	-	1.8	4.7	-	2.2	6.5	7.9	0.6	2.0	2.7	5.6	A+
9	9	-	2.7	2.7	-	2.2	5.3	7.1	0.6	1.6	2.4	5.6	A+
9	12	-	2.6	3.4	-	2.2	6.0	7.5	0.6	1.9	2.6	5.6	A+
9	18	-	2.3	4.5	-	2.2	6.8	7.9	0.6	2.1	2.7	5.6	A+
12	12	-	3.2	3.2	-	2.2	6.3	7.7	0.6	1.9	2.6	5.6	A+
12	18	-	2.7	4.1	-	2.2	6.8	7.9	0.6	2.1	2.7	5.6	A+
7	7	7	2.4	2.4	2.4	2.8	7.3	8.7	0.8	2.3	2.9	6.1	A++
7	7	9	2.3	2.3	2.9	2.8	7.4	8.7	0.8	2.3	2.9	6.1	A++
7	7	12	2.1	2.1	3.6	2.8	7.9	8.7	0.8	2.4	2.9	6.1	A++
7	9	9	2.1	2.7	2.7	2.8	7.6	8.7	0.8	2.4	2.9	6.1	A++
7	9	12	2.0	2.5	3.4	2.8	7.9	8.7	0.8	2.4	2.9	6.1	A++
7	12	12	1.8	3.1	3.1	2.8	7.9	8.7	0.8	2.4	2.9	6.1	A++
9	9	9	2.6	2.6	2.6	2.8	7.9	8.7	0.8	2.4	2.9	6.1	A++
9	9	12	2.4	2.4	3.2	2.8	7.9	8.7	0.8	2.4	2.9	6.1	A++
9	12	12	2.2	2.9	2.9	2.8	7.9	8.7	0.8	2.4	2.9	6.1	A++
12	12	12	2.6	2.6	2.6	2.8	7.9	8.7	0.8	2.4	2.9	6.1	A++

CHAUD													
Combinaison Unité Int			Capacité nominale (kW)			Capacité calorifique (kW)			Puissance absorbée (kW)			SCOP	Class. Energ.
A	B	C	A	B	C	Min.	Nom.	Max	Min	Nom	Max		
7	-	-	2.5	-	-	1.6	2.5	2.9	0.4	0.7	0.8	-	-
9	-	-	3.0	-	-	1.6	3.0	3.2	0.4	0.8	1.0	-	-
12	-	-	3.8	-	-	1.6	3.8	3.9	0.4	1.0	1.2	-	-
18	-	-	5.2	-	-	1.9	5.2	7.2	0.5	1.4	1.6	-	-
7	7	-	2.5	2.5	-	2.3	5.0	6.6	0.6	1.3	1.9	3.8	A
7	9	-	2.5	3.2	-	2.3	5.6	7.0	0.6	1.5	2.0	3.8	A
7	12	-	2.2	3.8	-	2.3	6.0	7.4	0.6	1.6	2.2	3.8	A
7	18	-	2.0	5.0	-	2.3	7.0	8.2	0.6	1.9	2.4	3.8	A
9	9	-	3.0	3.0	-	2.3	6.0	7.4	0.6	1.6	2.2	3.8	A
9	12	-	2.7	3.6	-	2.3	6.3	7.8	0.6	1.7	2.3	3.8	A
9	18	-	2.3	4.7	-	2.3	7.0	8.2	0.6	1.9	2.4	3.8	A
12	12	-	3.3	3.3	-	2.3	6.5	8.0	0.6	1.8	2.4	3.8	A
12	18	-	2.8	4.2	-	2.3	7.0	8.2	0.6	1.9	2.4	3.8	A
7	7	7	2.3	2.3	2.3	2.9	6.8	9.8	0.7	1.8	2.7	4.0	A+
7	7	9	2.1	2.1	2.7	2.9	7.0	9.8	0.7	1.9	2.7	4.0	A+
7	7	12	2.1	2.1	3.6	2.9	7.9	9.8	0.7	2.1	2.7	4.0	A+
7	9	9	2.2	2.8	2.8	2.9	7.9	9.8	0.7	2.1	2.7	4.0	A+
7	9	12	2.1	2.6	3.5	2.9	8.2	9.8	0.7	2.2	2.7	4.0	A+
7	12	12	1.9	3.2	3.2	2.9	8.3	9.8	0.7	2.2	2.7	4.0	A+
9	9	9	2.7	2.7	2.7	2.9	8.2	9.8	0.7	2.2	2.7	4.0	A+
9	9	12	2.5	3.3	2.9	8.3	9.8	0.7	2.2	2.7	4.0	A+	
9	12	12	2.3	3.0	3.0	2.9	8.3	9.8	0.7	2.2	2.7	4.0	A+
12	12	12	2.8	2.8	2.8	2.9	8.3	9.8	0.7	2.2	2.7	4.0	A+



MULTI



Groupe 4 sorties

FROID																
Combinaison Unité Int				Capacité nominale (kW)				Capacité frigorifique (kW)				Puissance absorbée (kW)			SEER	Class. Energ.
A	B	C	D	A	B	C	D	Min.	Nom.	Max	Min	Nom	Max			
7	-	-	-	2.0	-	-	-	1.6	2.0	2.9	0.5	0.6	0.8	-	-	
9	-	-	-	2.5	-	-	-	1.6	2.5	3.2	0.5	0.8	1.0	-	-	
12	-	-	-	3.5	-	-	-	1.6	3.5	3.9	0.5	1.1	1.3	-	-	
18	-	-	-	5.0	-	-	-	1.8	5.0	6.5	0.6	1.5	1.8	-	-	
24	-	-	-	7.0	-	-	-	2.2	7.0	8.0	0.6	2.1	2.5	-	-	
7	7	-	-	2.1	2.1	-	-	2.2	4.2	6.3	0.6	1.3	2.1	6.1	A++	
7	9	-	-	2.1	2.6	-	-	2.2	4.7	6.5	0.6	1.4	2.3	6.1	A++	
7	12	-	-	2.0	3.5	-	-	2.2	5.5	6.8	0.6	1.7	2.4	6.1	A++	
7	18	-	-	2.0	5.0	-	-	2.2	7.0	8.4	0.6	2.1	2.9	6.1	A++	
7	24	-	-	2.0	7.0	-	-	2.2	9.0	9.5	0.6	2.7	3.1	6.1	A++	
9	9	-	-	2.7	2.7	-	-	2.2	5.3	6.8	0.6	1.6	2.4	6.1	A++	
9	12	-	-	2.6	3.4	-	-	2.2	6.0	7.4	0.6	1.8	2.6	6.1	A++	
9	18	-	-	2.5	5.0	-	-	2.2	7.5	9.5	0.6	2.3	2.9	6.1	A++	
9	24	-	-	2.6	6.9	-	-	2.2	9.5	10.0	0.6	2.9	3.1	6.1	A++	
12	12	-	-	3.5	3.5	-	-	2.2	7.0	7.9	0.6	2.1	2.8	6.1	A++	
12	18	-	-	3.4	5.1	-	-	2.2	8.5	10.0	0.6	2.6	2.9	6.1	A++	
12	24	-	-	3.3	6.7	-	-	2.2	10.0	10.5	0.6	3.1	3.2	6.1	A++	
18	18	-	-	5.0	5.0	-	-	2.2	10.0	10.5	0.6	3.1	3.3	6.1	A++	
7	7	7	-	2.0	2.0	2.0	-	2.8	6.0	7.4	0.8	1.8	2.9	6.3	A++	
7	7	9	-	2.0	2.0	2.5	-	2.8	6.5	7.9	0.8	2.0	3.1	6.3	A++	
7	7	12	-	2.0	2.0	3.5	-	2.8	7.5	8.9	0.8	2.3	3.3	6.3	A++	
7	7	18	-	2.0	2.0	5.1	-	2.8	9.0	11.6	0.8	2.7	3.6	6.3	A++	
7	7	24	-	1.8	1.8	6.3	-	2.8	10.0	11.6	0.8	3.1	3.6	6.3	A++	
7	9	9	-	2.0	2.5	2.5	-	2.8	7.0	8.9	0.8	2.1	3.3	6.3	A++	
7	9	12	-	2.0	2.6	3.4	-	2.8	8.0	10.0	0.8	2.4	3.4	6.3	A++	
7	9	18	-	2.0	2.5	5.0	-	2.8	9.5	11.6	0.8	2.9	3.6	6.3	A++	
7	9	24	-	1.8	2.3	6.0	-	2.8	10.0	11.6	0.8	3.1	3.6	6.3	A++	
7	12	12	-	2.0	3.5	3.5	-	2.8	9.0	10.5	0.8	2.8	3.4	6.3	A++	
7	12	18	-	1.9	3.2	4.9	-	2.8	10.0	11.6	0.8	3.1	3.6	6.3	A++	
7	12	24	-	1.6	2.8	5.6	-	2.8	10.0	11.6	0.8	3.1	3.6	6.3	A++	
7	18	18	-	1.6	4.2	4.2	-	2.8	10.0	11.6	0.8	3.1	3.6	6.3	A++	
9	9	9	-	2.5	2.5	2.5	-	2.8	7.5	10.0	0.8	2.3	3.4	6.3	A++	
9	9	12	-	2.6	2.6	3.4	-	2.8	8.5	10.5	0.8	2.6	3.4	6.3	A++	
9	9	18	-	2.5	2.5	5.0	-	2.8	10.0	11.6	0.8	3.1	3.6	6.3	A++	
9	9	24	-	2.1	2.1	5.7	-	2.8	10.0	11.6	0.8	3.1	3.6	6.3	A++	
9	12	12	-	2.6	3.5	3.5	-	2.8	9.5	11.6	0.8	2.9	3.6	6.3	A++	
9	12	18	-	2.3	3.1	4.6	-	2.8	10.0	11.6	0.8	3.1	3.6	6.3	A++	
9	12	24	-	2.0	2.7	5.3	-	2.8	10.0	11.6	0.8	3.1	3.6	6.3	A++	
9	18	18	-	2.0	4.0	4.0	-	2.8	10.0	11.6	0.8	3.1	3.6	6.3	A++	
12	12	12	-	3.3	3.3	3.3	-	2.8	10.0	11.6	0.8	3.1	3.6	6.3	A++	
12	12	18	-	2.9	2.9	4.3	-	2.8	10.0	11.6	0.8	3.1	3.6	6.3	A++	
7	7	7	7	2.1	2.1	2.1	2.1	3.7	8.2	10.5	0.9	2.3	3.3	6.5	A++	
7	7	7	9	2.0	2.0	2.0	2.6	3.7	8.5	11.6	0.9	2.5	3.4	6.5	A++	
7	7	7	12	2.0	2.0	2.0	3.5	3.7	9.5	12.6	0.9	2.9	3.8	6.5	A++	
7	7	7	18	1.9	1.9	1.9	4.8	3.7	10.4	13.7	0.9	3.2	4.0	6.5	A++	
7	7	9	9	2.0	2.0	2.5	2.5	3.7	9.0	12.6	0.9	2.7	3.8	6.5	A++	
7	7	9	12	2.0	2.0	2.6	3.4	3.7	10.0	13.1	0.9	3.1	3.9	6.5	A++	
7	7	9	18	1.8	1.8	2.3	4.6	3.7	10.5	13.7	0.9	3.3	4.0	6.5	A++	
7	7	12	12	1.9	1.9	3.3	3.3	3.7	10.5	13.7	0.9	3.3	4.0	6.5	A++	
7	7	12	18	1.7	1.7	2.9	4.3	3.7	10.5	13.7	0.9	3.3	4.0	6.5	A++	
7	9	9	9	2.0	2.5	2.5	2.5	3.7	9.5	13.1	0.9	2.9	3.8	6.5	A++	
7	9	9	12	2.0	2.6	2.6	3.4	3.7	10.5	13.7	0.9	3.3	4.0	6.5	A++	
7	9	9	18	1.7	2.2	2.2	4.4	3.7	10.5	13.7	0.9	3.3	4.0	6.5	A++	
7	9	12	12	1.8	2.4	3.2	3.2	3.7	10.5	13.7	0.9	3.3	4.0	6.5	A++	
7	12	12	12	1.7	2.9	2.9	3.7	10.5	13.7	0.9	3.3	4.0	6.5	A++		
9	9	9	9	2.6	2.6	2.6	2.6	3.7	10.5	13.7	0.9	3.3	4.0	6.5	A++	
9	9	9	12	2.4	2.4	2.4	3.2	3.7	10.5	13.7	0.9	3.3	4.0	6.5	A++	
9	9	9	18	2.1	2.1	2.1	4.2	3.7	10.5	13.7	0.9	3.3	4.0	6.5	A++	
9	9	12	12	2.3	2.3	3.0	3.0	3.7	10.5	13.7	0.9	3.3	4.0	6.5	A++	
9	12	12	12	2.1	2.8	2.8	2.8	3.7	10.5	13.7	0.9	3.3	4.0	6.5	A++	
12	12	12	12	2.6	2.6	2.6	2.6	3.7	10.5	13.7	0.9	3.3	4.0	6.5	A++	

CHAUD															
Combinaison Unité Int				Capacité nominale (kW)				Capacité calorifique (kW)			Puissance absorbée (kW)			SEER	Class. Energ.
A	B	C	D	A	B	C	D	Min.	Nom.	Max	Min	Nom	Max		
7	-	-	-	2.5	-	-	-	1.7	2.5	2.9	0.5	0.7	0.8	-	-
9	-	-	-	3.0	-	-	-	1.7	3.0	3.2	0.5	0.8	1.0	-	-
12	-	-	-	3.8	-	-	-	1.7	3.8	3.9	0.5	1.0	1.2	-	-
18	-	-	-	5.2	-	-	-	1.9	5.2	7.0	0.6	1.4	1.6	-	-
24	-	-	-	7.2	-	-	-	1.9	7.2	8.0	0.6	1.9	2.2	-	-
7	7	-	-	2.5	2.5	-	-	2.3	5.0	6.7	0.6	1.3	1.9	3.5	A
7	9	-	-	2.5	3.2	-	-	2.3	5.6	6.9	0.6	1.5	2.1	3.5	A
7	12	-	-	2.2	3.8	-	-	2.3	6.0	7.2	0.6	1.6	2.2	3.5	A
7	18	-	-	2.2	5.8	-	-	2.3	8.0	8.9	0.6	2.2	2.6	3.4	A
7	24	-	-	2.2	7.4	-	-	2.3	9.6	10.8	0.6	2.6	2.8	3.4	A
9	9	-	-	3.0	3.0	-	-	2.3	6.0	7.2	0.6	1.6	2.2	3.5	A
9	12	-	-	3.0	4.0	-	-	2.3	7.0	7.8	0.6	1.9	2.4	3.5	A
9	18	-	-	2.7	5.9	-	-	2.3	8.8	10.0	0.6	2.4	2.7	3.4	A
9	24	-	-	2.7	7.1	-	-	2.3	9.8	10.7	0.6	2.6	2.8	3.4	A
12	12	-	-	3.8	3.8	-	-	2.3	7.5	8.3	0.6	2.0	2.5	3.5	A
12	18	-	-	3.8	5.6	-	-	2.3	9.4	10.5	0.6	2.5	2.7	3.4	A
12	24	-	-	3.3	6.7	-	-	2.3	10.0	10.9	0.6	2.7	2.9	3.4	A
18	18	-	-	5.1	5.1	-	-	2.3	10.1	11.1	0.6	2.7	3.0	3.6	A
7	7	7	-	2.5	2.5										

TABLEAUX DE COMBINAISON

Groupe 5 sorties

FROID																	
Combinaison Unité Int					Capacité nominale (kW)			Capacité frigorifique (kW)		Puissance absorbée (kW)			SEER	Class. Energ.			
A	B	C	D	E	A	B	C	D	E	Min.	Nom.	Max	Min	Nom	Max		
7	-	-	-	-	2.0	-	-	-	-	1.7	2.0	2.9	0.5	0.6	0.8	-	-
9	-	-	-	-	2.5	-	-	-	-	1.7	2.5	3.2	0.5	0.8	1.0	-	-
12	-	-	-	-	3.5	-	-	-	-	1.7	3.5	3.9	0.5	1.1	1.3	-	-
18	-	-	-	-	5.0	-	-	-	-	1.8	5.0	6.5	0.6	1.5	1.8	-	-
24	-	-	-	-	7.0	-	-	-	-	2.1	7.0	8.2	0.7	2.2	2.3	-	-
7	7	-	-	-	2.1	2.1	-	-	-	2.3	4.2	7.4	0.6	1.3	2.2	5.6	A+
7	9	-	-	-	2.1	2.6	-	-	-	2.3	4.7	7.6	0.6	1.5	2.4	5.6	A+
7	12	-	-	-	2.0	3.5	-	-	-	2.3	5.5	8.0	0.6	1.7	2.5	5.6	A+
7	18	-	-	-	2.0	5.0	-	-	-	2.3	7.0	9.8	0.6	2.2	2.7	5.6	A+
7	24	-	-	-	2.1	7.0	-	-	-	2.3	9.1	11.7	0.6	2.8	3.0	5.6	A+
9	9	-	-	-	2.7	2.7	-	-	-	2.3	5.3	8.0	0.6	1.6	2.5	5.6	A+
9	12	-	-	-	2.6	3.4	-	-	-	2.3	6.0	8.6	0.6	1.9	2.6	5.6	A+
9	18	-	-	-	2.5	5.0	-	-	-	2.3	7.5	11.1	0.6	2.3	2.8	5.6	A+
9	24	-	-	-	2.6	7.1	-	-	-	2.3	9.7	12.3	0.6	3.0	3.2	5.6	A+
12	12	-	-	-	3.5	3.5	-	-	-	2.3	7.0	9.2	0.6	2.2	2.7	5.6	A+
12	18	-	-	-	3.4	5.1	-	-	-	2.3	8.5	11.7	0.6	2.6	3.1	5.6	A+
12	24	-	-	-	3.3	6.7	-	-	-	2.3	10.0	12.3	0.6	3.1	3.4	5.6	A+
18	18	-	-	-	5.3	5.3	-	-	-	2.3	10.5	12.3	0.6	3.3	3.4	5.6	A+
7	7	-	-	-	2.0	2.0	2.0	-	-	2.9	6.0	7.4	0.8	1.8	3.0	5.8	A+
7	7	9	-	-	2.0	2.0	2.5	-	-	2.9	6.5	8.6	0.8	2.0	3.2	5.8	A+
7	7	12	-	-	2.0	2.0	3.5	-	-	2.9	7.5	9.2	0.8	2.3	3.4	5.8	A+
7	7	18	-	-	2.0	2.0	5.1	-	-	2.9	9.0	11.1	0.8	2.8	3.6	5.8	A+
7	7	24	-	-	2.0	2.0	6.9	-	-	2.9	11.0	12.9	0.8	3.4	3.8	5.8	A+
7	9	9	-	-	2.0	2.5	2.5	-	-	2.9	7.0	9.2	0.8	2.2	3.3	5.8	A+
7	9	12	-	-	2.0	2.6	3.4	-	-	2.9	8.0	10.5	0.8	2.5	3.5	5.8	A+
7	9	18	-	-	2.0	2.5	5.0	-	-	2.9	9.5	11.1	0.8	2.9	3.7	5.8	A+
7	9	24	-	-	2.0	2.6	6.9	-	-	2.9	11.5	12.9	0.8	3.6	3.9	5.8	A+
7	12	12	-	-	2.0	3.5	3.5	-	-	2.9	9.0	11.1	0.8	2.8	3.6	5.8	A+
7	12	18	-	-	2.0	3.4	5.1	-	-	2.9	10.5	12.3	0.8	3.3	3.8	5.8	A+
7	12	24	-	-	1.9	3.2	6.4	-	-	2.9	11.5	12.9	0.8	3.6	3.9	5.8	A+
7	18	18	-	-	1.9	4.8	4.8	-	-	2.9	11.5	12.9	0.8	3.6	3.9	5.8	A+
9	9	9	-	-	2.7	2.7	2.7	-	-	2.9	8.0	10.5	0.8	2.5	3.8	5.8	A+
9	9	12	-	-	2.7	2.7	3.6	-	-	2.9	9.0	12.9	0.8	2.8	3.6	5.8	A+
9	9	18	-	-	2.6	2.6	5.3	-	-	2.9	10.5	12.3	0.8	3.3	3.8	5.8	A+
9	9	24	-	-	2.5	2.5	6.6	-	-	2.9	11.5	12.9	0.8	3.6	3.9	5.8	A+
9	12	12	-	-	2.5	3.3	3.3	-	-	2.9	9.0	11.1	0.8	2.8	3.6	5.8	A+
9	12	18	-	-	2.5	3.4	5.1	-	-	2.9	11.0	11.7	0.8	3.4	3.8	5.8	A+
9	12	24	-	-	2.3	3.1	6.1	-	-	2.9	11.5	12.9	0.8	3.6	3.9	5.8	A+
9	18	18	-	-	2.4	4.8	4.8	-	-	2.9	12.0	12.9	0.8	3.7	3.9	5.8	A+
12	12	12	-	-	3.2	3.2	3.2	-	-	2.9	9.5	11.1	0.8	2.9	3.7	5.8	A+
12	12	18	-	-	3.3	3.3	4.9	-	-	2.9	11.5	12.9	0.8	3.6	3.9	5.8	A+
12	12	24	-	-	3.0	3.0	6.0	-	-	2.9	12.0	12.9	0.8	3.7	3.9	5.8	A+
12	18	18	-	-	3.0	4.5	4.5	-	-	2.9	12.0	12.9	0.8	3.7	3.9	5.8	A+

CHAUD																	
Combinaison Unité Int					Capacité nominale (kW)			Capacité calorifique (kW)		Puissance absorbée (kW)		SEER	Class. Energ.				
A	B	C	D	E	A	B	C	D	E	Min.	Nom.	Max					
7	-	-	-	-	2.5	-	-	-	-	1.7	2.5	2.9	0.5	0.7	0.8	-	-
9	-	-	-	-	3.0	-	-	-	-	1.7	3.0	3.2	0.5	0.8	1.0	-	-
12	-	-	-	-	3.8	-	-	-	-	1.7	3.8	3.9	0.5	1.0	1.2	-	-
18	-	-	-	-	5.2	-	-	-	-	1.8	5.2	7.0	0.6	1.4	1.6	-	-
24	-	-	-	-	7.2	-	-	-	-	2.1	7.2	8.5	0.7	1.9	2.0	-	-
7	7	-	-	-	2.5	2.5	-	-	-	2.3	5.0	7.4	0.6	1.3	1.9	3.6	A
7	9	-	-	-	2.5	3.2	-	-	-	2.3	5.6	7.6	0.6	1.5	2.0	3.6	A
7	12	-	-	-	2.2	3.8	-	-	-	2.3	6.0	8.0	0.6	1.6	2.2	3.6	A
7	18	-	-	-	2.2	5.8	-	-	-	2.3	8.0	9.8	0.6	2.2	2.3	3.6	A
7	24	-	-	-	2.2	7.6	-	-	-	2.3	9.8	11.7	0.6	2.6	2.6	3.6	A
9	9	-	-	-	3.0	3.0	-	-	-	2.3	6.0	8.0	0.6	1.6	2.2	3.6	A
9	12	-	-	-	2.9	3.9	-	-	-	2.3	6.8	8.6	0.6	1.8	2.2	3.6	A
9	18	-	-	-	2.9	5.9	-	-	-	2.3	8.8	11.1	0.6	2.4	2.5	3.6	A
9	24	-	-	-	2.8	7.4	-	-	-	2.3	10.2	12.3	0.6	2.7	2.8	3.6	A
12	12	-	-	-	3.8	3.8	-	-	-	2.3	7.5	9.2	0.6	2.0	2.3	3.6	A
12	18	-	-	-	3.8	5.6	-	-	-	2.3	9.4	11.7	0.6	2.5	2.7	3.8	A
12	24	-	-	-	3.5	7.0	-	-	-	2.3	10.5	12.3	0.6	2.8	3.0	3.8	A
18	18	-	-	-	5.5	5.5	-	-	-	2.3	11.0	12.3	0.6	3.0	3.0	3.8	A
7	7	7	-	-	2.5	2.5	2.5	-	-	2.9	7.5	8.6	0.7	2.0	2.6	3.6	A
7	7	9	-	-	2.4	2.4	3.1	-	-	2.9	7.8	9.2	0.7	2.1	2.8	3.6	A
7	7	12	-	-	2.3	2.3	3.9	-	-	2.9	8.5	9.8	0.7	2.3	3.0	3.6	A
7	7	18	-	-	2.5	2.5	6.5	-	-	2.9	11.5	12.3	0.7	3.1	3.1	3.5	A
7	7	24	-	-	2.2	2.2	7.6	-	-	2.9	12.0	12.9	0.7	3.2	3.3	3.4	A
7	9	9	-	-	2.4	3.1	3.1	-	-	2.9	8.5	9.8	0.7	2.3	2.9	3.6	A
7	9	12	-	-	2.5	4.3	4.3	-	-	2.9	10.0	12.3	0.7	2.7	3.0	3.6	A
7	9	18	-	-	2.4	3.0	6.1	-	-	2.9	11.5	12.3	0.7	3.1	3.2	3.5	A
7	9	24	-	-	2.1	2.7	7.2	-	-	2.9	12.0	12.9	0.7	3.2	3.4	3.6	A
7	12	12	-	-	2.5	4.3	4.3	-	-	2.9	11.0	12.3	0.7	3.0	3.1	3.6	A
7	12	18	-	-	2.2	3.7	5.6	-	-	2.9	11.5	12.3	0.7	3.1	3.3	3.6	A
7	12	24	-	-	2.0	3.3	6.7	-	-	2.9	12.0	12.9	0.7	3.2	3.4	3.6	A
7	18	18	-	-	2.0	5.0	5.0	-	-	2.9	12.0	12.9	0.7	3.2	3.4	3.6	A
9	9	9	-	-	3.3</												



MULTI



Groupe 5 sorties (suite)

FROID										CHAUD																									
Combinaison Unité Int					Capacité nominale (kW)				Capacité frigorifique (kW)			Puissance absorbée (kW)			SEER	Class. Energ.	Combinaison Unité Int					Capacité nominale (kW)				Capacité calorifique (kW)			Puissance absorbée (kW)			SEER	Class. Energ.		
A	B	C	D	E	A	B	C	D	E	Min.	Nom.	Max	Min.	Nom.	Max		A	B	C	D	E	Min.	Nom.	Max	Min.	Nom.	Max	Min.	Nom.	Max					
7	7	7	7	-	2.0	2.0	2.0	2.0	-	3.7	8.0	10.5	0.9	2.5	3.4	6.1	A++	7	7	7	7	-	2.5	2.5	2.5	-	3.7	10.0	12.7	0.8	2.7	3.0	3.8	A	
7	7	7	9	-	2.0	2.0	2.0	2.6	-	3.7	8.5	11.1	0.9	2.6	3.6	6.1	A++	7	7	7	9	-	2.6	2.6	2.6	3.3	-	3.7	11.0	12.9	0.8	3.0	3.1	3.8	A
7	7	7	12	-	2.0	2.0	2.0	3.5	-	3.7	9.5	11.7	0.9	2.9	3.7	6.1	A++	7	7	7	12	-	2.5	2.5	2.5	4.3	-	3.7	11.8	13.5	0.8	3.2	3.2	3.7	A
7	7	7	18	-	2.1	2.1	2.1	5.3	-	3.7	11.5	12.3	0.9	3.6	4.2	6.1	A++	7	7	7	18	-	2.2	2.2	2.2	5.5	-	3.7	12.0	13.5	0.8	3.2	3.6	3.6	A
7	7	7	24	-	1.9	1.9	1.9	6.4	-	3.7	12.0	13.5	0.9	3.7	4.4	6.1	A++	7	7	7	24	-	1.9	1.9	1.9	6.6	-	3.7	12.3	13.5	0.8	3.3	3.8	3.4	A
7	7	9	9	-	2.1	2.1	2.7	2.7	-	3.7	9.5	11.7	0.9	2.9	3.7	6.1	A++	7	7	9	9	-	2.6	2.6	3.4	3.4	-	3.7	12.0	13.5	0.8	3.2	3.2	3.6	A
7	7	9	12	-	2.0	2.0	2.6	3.4	-	3.7	10.0	12.3	0.9	3.1	4.2	6.1	A++	7	7	9	12	-	2.4	2.4	3.1	4.1	-	3.7	12.0	13.5	0.8	3.2	3.6	3.6	A
7	7	9	18	-	2.0	2.0	2.5	5.0	-	3.7	11.5	12.3	0.9	3.6	4.2	6.1	A++	7	7	9	18	-	2.0	2.0	2.6	5.3	-	3.7	12.0	13.5	0.8	3.2	3.6	3.5	A
7	7	9	24	-	1.8	1.8	2.3	6.1	-	3.7	12.0	13.5	0.9	3.7	4.4	6.1	A++	7	7	9	24	-	1.8	1.8	2.4	6.3	-	3.7	12.3	13.5	0.8	3.3	3.8	3.4	A
7	7	12	12	-	1.9	1.9	3.3	3.3	-	3.7	10.5	12.9	0.9	3.3	4.2	6.1	A++	7	7	12	12	-	2.2	2.2	3.8	3.8	-	3.7	12.0	13.5	0.8	3.2	3.6	3.6	A
7	7	12	18	-	1.8	1.8	3.1	4.7	-	3.7	11.5	13.5	0.9	3.6	4.2	6.1	A++	7	7	12	18	-	1.9	1.9	3.3	4.9	-	3.7	12.0	13.5	0.8	3.2	3.6	3.5	A
7	7	12	24	-	1.7	1.7	3.0	5.9	-	3.7	12.3	13.5	0.9	3.8	4.4	6.1	A++	7	7	12	24	-	1.7	1.7	3.0	5.9	-	3.7	12.3	13.5	0.8	3.3	3.8	3.4	A
7	9	9	9	-	2.1	2.6	2.6	2.6	-	3.7	10.0	12.3	0.9	3.1	4.2	6.1	A++	7	7	18	18	-	1.7	1.7	4.3	4.3	-	3.7	12.0	13.5	0.8	3.2	3.8	3.4	A
7	9	9	12	-	2.0	2.6	2.6	3.4	-	3.7	10.5	12.9	0.9	3.3	4.2	6.1	A++	7	9	9	9	-	2.5	3.2	3.2	3.2	-	3.7	12.0	13.5	0.8	3.2	3.6	3.7	A
7	9	9	18	-	1.9	2.4	2.4	4.8	-	3.7	11.5	13.5	0.9	3.6	4.2	6.1	A++	7	9	9	12	-	2.3	2.9	2.9	3.9	-	3.7	12.0	13.5	0.8	3.2	3.6	3.5	A
7	9	9	24	-	1.8	2.3	2.3	6.0	-	3.7	12.3	13.5	0.9	3.8	4.4	6.1	A++	7	9	9	18	-	2.0	2.5	2.5	5.0	-	3.7	12.0	13.5	0.8	3.2	3.6	3.5	A
7	9	12	12	-	2.0	2.6	3.5	3.5	-	3.7	11.5	13.5	0.9	3.6	4.2	6.1	A++	7	9	9	24	-	1.8	2.3	2.3	6.0	-	3.7	12.3	13.5	0.8	3.3	3.8	3.4	A
7	9	12	18	-	1.8	2.3	3.1	4.7	-	3.7	12.0	13.5	0.9	3.7	4.4	6.1	A++	7	9	12	12	-	2.1	2.7	3.6	3.6	-	3.7	12.0	13.5	0.8	3.2	3.6	3.4	A
7	9	12	24	-	1.7	2.1	2.8	5.7	-	3.7	12.3	13.5	0.9	3.8	4.4	6.1	A++	7	9	12	18	-	1.8	2.3	3.1	4.7	-	3.7	12.0	13.5	0.8	3.2	3.8	3.5	A
7	9	18	18	-	1.7	2.1	4.3	4.3	-	3.7	12.3	13.5	0.9	3.8	4.4	6.1	A++	7	9	12	24	-	1.7	2.1	2.8	5.7	-	3.7	12.3	13.5	0.8	3.3	3.8	3.4	A
7	9	18	24	-	1.5	1.9	3.8	5.1	-	3.7	12.3	13.5	0.9	3.8	4.4	6.1	A++	7	9	18	18	-	1.6	2.1	4.2	4.2	-	3.7	12.0	13.5	0.8	3.2	3.8	3.5	A
7	12	12	12	-	1.9	3.2	3.2	3.2	-	3.7	11.5	13.5	0.9	3.6	4.2	6.1	A++	7	12	12	12	-	2.0	3.3	3.3	3.3	-	3.7	12.0	13.5	0.8	3.2	3.6	3.4	A
7	12	12	18	-	1.7	2.9	2.9	4.4	-	3.7	12.0	13.5	0.9	3.7	4.4	6.1	A++	7	12	12	18	-	1.7	2.9	4.4	4.4	-	3.7	12.0	13.5	0.8	3.2	3.8	3.5	A
9	9	9	9	-	2.6	2.6	2.6	2.6	-	3.7	10.5	12.9	0.9	3.3	4.2	6.1	A++	9	9	9	9	-	3.0	3.0	3.0	3.0	-	3.7	12.0	13.5	0.8	3.2	3.6	3.8	A
9	9	9	12	-	2.7	2.7	2.7	3.5	-	3.7	11.5	13.5	0.9	3.6	4.2	6.1	A++	9	9	9	12	-	2.8	2.8	3.7	3.7	-	3.7	12.0	13.5	0.8	3.2	3.6	3.7	A
9	9	9	18	-	2.4	2.4	2.4	4.8	-	3.7	12.0	13.5	0.9	3.7	4.4	6.1	A++	9	9	9	18	-	2.4	2.4	2.4	4.8	-	3.7	12.0	13.5	0.8	3.2	3.8	3.6	A
9	9	9	24	-	2.2	2.2	2.2	5.8	-	3.7	12.3	13.5	0.9	3.8	4.4	6.1	A++	9	9	9	24	-	2.2	2.2	2.2	5.8	-	3.7	12.3	13.5	0.8	3.3	3.8	3.4	A
9	9	12	12	-	2.5	2.5	3.3	3.3	-	3.7	11.5	13.5	0.9	3.6	4.2	6.1	A++	9	9	12	12	-	2.6	2.6	3.4	3.4	-	3.7	12.0	13.5	0.8	3.2	3.6	3.5	A
9	9	12	18	-	2.3	2.3	3.0	4.5	-	3.7	12.0	13.5	0.9	3.7	4.4	6.1	A++	9	9	12	18	-	2.3	2.3	3.0	4.5	-	3.7	12.0	13.5	0.8	3.2	3.8	3.5	A
9	9	12	24	-	2.1	2.1	2.7	5.5	-	3.7	12.3	13.5	0.9	3.8	4.4	6.1	A++	9	9	12	24	-	2.7	2.7	5.5	5.5	-	3.7	12.3	13.5	0.8	3.3	3.8	3.4	A
9	12	12	12	-	2.3	3.1	3.1	3.1	-	3.7	11.5	13.5	0.9	3.6	4.2	6.1	A++	9	12	12	12	-	2.4	3.2	3.2	3.2	-	3.7	12.0	13.5	0.8	3.2	3.6	3.6	A
9	12	12	18	-	2.2	2.9	2.9	4.3	-	3.7	12.3	13.5	0.9	3.8	4.4	6.1	A++	9	12	12	18	-	2.1	2.8	2.8	4.2	-	3.7	12.0	13.5	0.8	3.2	3.8	3.5	A
12	12	12	12	-	2.9	2.9	2.9	2.9	-	3.7	11.5	13.5	0.9	3.6	4.2	6.1	A++	12	12	12	12	-	3.0	3.0	3.0	3.0	-	3.7	12.0	13.5	0.8	3.2	3.6	3.6	A
12	12	12	18	-	2.7	2.7	2.7	4.1	-	3.7	12.3	13.5	0.9	3.8	4.4	6.1	A++	12	12	12	18	-	2.7	2.7	2.7	4.0	-	3.7	12.0	13.5	0.8	3.2	3.8	3.5	A
7	7	7	7	7	2.1	2.1	2.1	2.1	2.1	4.2	10.5	14.0	1.0	3.1	4.6	6.6	A++	7	7	7	7	7	2.5	2.5	2.5	2.5	2.5	4.2	12.3	14.9	0.9	3.3	4.1	3.8	A
7	7	7	7	18	1.9	1.9	1.9	4.8	4.2	12.3	14.0	1.0	3.8	4.6	6.6	A++	7	7	7	7	18	1.9	1.9	1.9	4.8	4.2	4.2	12.3	14.9	0.9	3.3	4.1	3.8	A	
7	7	7	9	9	2.1	2.1	2.1	2																											