



UNITES INTERIEURES COMPATIBLES

GAINABLE v3 pour MULTI

2.5 KW 3.5 KW 5 KW 7 KW





GAINABLE pour MULTI			IDS 092 2.5kW	IDS 122 3.5kW	IDS 182 5kW	IDS 242 7kW
Mode Froid	Puissance	kW	2.6	3.5	5.3	7.1
	Puissance nominale absorbée/Consommation	kW	0,72 (0,13~1,18)	1,16 (0,15 - 1,46)	1,59 (0,36 - 2,13)	2,28 (0,75 - 2,86)
Mode Chaud	Puissance	kW	2.8	2.9	5.2	6.5
	Puissance nominale absorbée/Consommation	kW	0,85 (0,3 - 0,85)	1,28 (0,3 - 1,42)	1,61 (0,5 - 1,85)	2,0 (0,64 - 2,50)
Certication EUROVENT			1	OUI	OUI	OUI

Unités intérieures		IDSV 092DRIV3	IDSV 122DRIV3	IDSV 182DRIV3	IDSV 242DRIV3
Débit d'air	m3/h	620/540/450	660/570/470	900/780/650	1200/1000/700
Vitesse	r/min	1130/1047/965	1140/1052/965	1000/900/800	950/850/750
Niveau sonore	dB(A)	35/33/31/27	35/33/31/26	36/34/31	33/32/31
Cable d'interconection UI UE		4 x 1,5	4 x 1,5	4 x 1,5	4 x 1,5
Liaison frigorifique	pouce	1/4 - 3/8	1/4 - 3/8	1/4 - 1/2	3/8 - 5/8
Dimensions nettes (LxPxH)	mm	700x450x200	700x450x200	700x750x245	1000x750x245
Poids net	Kg	16,6	16,6	24,4	31,8
Télécommande	Télécommande Infrarouge et Télécommande filaire, avec programmation hebdomadaire / interface N2 livrées de série				





En série

En série